

## IKOpro Quick Dry Bitumen Primer

### Fast Drying Primer Bituminous Membranes

#### Product Details

<b>Product</b>	IKOpro Quick Dry Bitumen Primer
<b>Tin Volume</b>	5 / 25 litres
<b>Colour</b>	Black
<b>Product Codes</b>	MW646405 & MW646408



#### Introduction

Fast-drying bitumen priming solution designed to seal and prepare dry or slightly damp substrates surfaces for the application of bitumen waterproofing products and systems. Drying time approximately 30 minutes at 20°C, depending on the substrate. No residual tack. May be applied to many substrates including concrete, brickwork, zinc, metal, and existing bitumen roofing. For use with bitumen membranes and liquid IKOpro maintenance products.

#### Features & Benefits

- Quick drying - primer dries within 30 minutes in good conditions

#### Storage

Containers should be kept sealed in a cool, dry, well ventilated environment and all practical precautions taken against fire. Partly used containers may be resealed and used again after correct storage. To avoid the risk of spillage, always store and transport in a secure upright position. IKOpro Quick Dry Primer has a shelf life of 3 months.

#### Application Rate

Substrate	m <sup>2</sup> per Litre
Metal	10 - 15
Bitumen	5
Concrete	3 - 4

## IKOpro Quick Dry Primer Application

1. Application temperature should be between +3 and +27°C ready for use.
2. All surfaces must be clean, dry and free from grease, oil, dirt and loose material. Smooth metal surfaces, where necessary, should be prepared with a wire brush. If moss or lichen is present this must be removed and the surface treated with IKOpro Algae and Fungi Remover applied in accordance with its application instructions before proceeding.
3. Apply IKOpro Quick Dry Bitumen Primer in one coat with a brush, roller or airless spray gun.
4. Apply a thin even coating, brushing well into the surface. Do not allow material to pool or collect in depressions.
5. Allow drying thoroughly before proceeding with the application of other bitumen products. Drying times may be extended in low temperatures.

**Note: Use only in well-ventilated areas, or with respiratory apparatus, away from all sources of ignition. Precautions must be taken to prevent the solvent vapour entering the ventilating systems of buildings.**

## Further Product Information

Full product literature and technical sheets are available as downloads from our website: [www.ikopolymeric.com](http://www.ikopolymeric.com) or on request by email: [polymeric.marketing@iko.com](mailto:polymeric.marketing@iko.com)

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued.

Company Registered in England No. 2678296 – Registered Office: Appley Lane North, Appley Bridge, Wigan, Lancashire, WN6 9AB



**n55Plus**

**IKO Polymeric**

Coney Green Road, Clay Cross  
Chesterfield, S45 9HZ

**Tel:** 01257 488 000

**Sales:** [polymeric.sales.uk@iko.com](mailto:polymeric.sales.uk@iko.com)

**Technical:** [polymeric.technical.uk@iko.com](mailto:polymeric.technical.uk@iko.com)